

BT7055

POLE FINISHING RING FOR 50MM POLES

- Escutcheon ring designed to improve the installed look of a ceiling or floor mounted pole
- Attractive appearance when used with a suspended ceiling
- Designed for 50mm (2") poles only
- **POLE SOLD SEPARATELY**
- **Available in Black**






BT7056

FLOOR FIXING KIT FOR 50MM POLES

- Allows poles to be fixed to the floor to stop lateral movement in a floor to ceiling installation
- Suitable for most floor types including concrete and wooden floors
- Chrome cover and fixing hardware included
- Kit comprises of three different solutions for optimum installation choice
- **POLE MUST BE SUSPENDED FROM A CEILING MOUNT**

Please note: When the load is taken by this product it is necessary to support the pole at the top as per a standard ceiling installation



	Fixing A	Fixing B	Fixing C
			
Recommended Installation	Load ideally suspended from the ceiling	Load taken by the floor or suspended from the ceiling	Load taken by the floor only
Fixing Method	Centre only	Centre or External	External only
Trim Ring	Optional	Advisable	Advisable
Features	Hidden fixings. Pole length tolerance up to minus 10mm.	Plate to spread load. Pole length tolerance up to minus 10mm.	Plate to spread load. Clear hole in centre to pass cables.



Registered Design No.
4003652
4003653

BT7025

COLLAR ADAPTOR FOR HORIZONTAL POLES

- Allows poles to be mounted horizontally across fixed vertical poles
- Suitable for 50mm (2") poles
- 50mm poles requires 3 x BT7051 heavy duty collars
- **The recommended weight limit of the BT7025 is 140Kg (70Kg each side of the BT7025). Individual weight limits of attached and supporting mounts must not be exceeded. As B-Tech has no control over how this product is used, it is important that installers ensure the structure is strong enough before attaching AV equipment and that the structure is counterbalanced at both ends of all horizontal poles. B-Tech accept no liability for loss or damage caused by improper installation or mounting on unstable structures.**
- **Available in Black**

