

BTXL23

STEREO AUDIO - STEREO AUDIO

- 2 RCA Audio plugs to 2 RCA audio plugs
- Designed for Stereo audio signals
- 24k Gold plated connectors for superior signal transfer
- Heavy duty nylon braided outer jacket protects cable
- Individually shielded and fully screened to eliminate RF and EM interference
- High grade O.F.C (Oxygen Free Copper) conductor for minimum signal loss
- **SUPPLIED IN PROFESSIONAL INSTALL ZIPPED BAG**



BTXL23
Available in the
following lengths

- 0.8m = BTXL23-008
- 1.5m = BTXL23-015
- 3.0m = BTXL23-030
- 5.0m = BTXL23-050
- 10.0m = BTXL23-100
- 15.0m = BTXL23-150

BTXL39

HDMI - HDMI

- HDMI™ male plug to HDMI™ male plug
- Capable of transferring full HD 1080p signals
- HDMI version 1.3 compliant
- 24k Gold plated connectors for superior signal transfer
- Robust moulded plugs
- Heavy duty nylon braided outer jacket protects cable
- Individually shielded and fully screened to eliminate RF and EM interference
- High grade O.F.C (Oxygen Free Copper) conductor for minimum signal loss
- **SUPPLIED IN PROFESSIONAL INSTALL ZIPPED BAG**



BTXL39
Available in the
following lengths

- 0.8m = BTXL39-008
- 1.5m = BTXL39-015
- 3.0m = BTXL39-030
- 5.0m = BTXL39-050
- 10.0m = BTXL39-100

BTXL41

HDMI - DVI

- HDMI™ male plug to DVI-D Dual link male plug (24 Pin + Flat Blade)
- 24k Gold plated connectors for superior signal transfer
- Robust moulded plugs
- Heavy duty nylon braided outer jacket protects cable
- Individually shielded and fully screened to eliminate RF and EM interference
- High grade O.F.C (Oxygen Free Copper) conductor for minimum signal loss
- Digital only
- **SUPPLIED IN PROFESSIONAL INSTALL ZIPPED BAG**



BTXL41
Available in the
following lengths

- 0.8m = BTXL41-008
- 1.5m = BTXL41-015
- 3.0m = BTXL41-030
- 5.0m = BTXL41-050
- 10.0m = BTXL41-100

BTXL43

DVI - DVI

- Dual Link DVI-D male plug to DVI-D Dual link male plug (24 Pin + Flat Blade)
- 24k Gold plated connectors for superior signal transfer
- Robust moulded plugs
- Heavy duty nylon braided outer jacket protects cable
- Individually shielded and fully screened to eliminate RF and EM interference
- High grade O.F.C (Oxygen Free Copper) conductor for minimum signal loss
- Digital only
- **SUPPLIED IN PROFESSIONAL INSTALL ZIPPED BAG**



BTXL43
Available in the
following lengths

- 0.8m = BTXL43-008
- 1.5m = BTXL43-015
- 3.0m = BTXL43-030
- 5.0m = BTXL43-050
- 10.0m = BTXL43-100

